

Ratings

Voltage: 60 V
 Temperature: -40~125 °C

Conductor

Conductor count: 1
 Gauge: 20 AWG 0.56 mm²
 Material: tinned copper strands
 Strand size: Ø0.32 mm x 7
 Resistance at 20 °C: 34.6 Ω /km max

Insulator

Material: XLPE
 Color: white
 Diameter: Ø 1.8 ±0.10 mm
 Nominal thickness: 0.4 mm



Wire marking: TXL AUTOMOTIVE PRIMARY WIRE 20 AWG XLPE
 125°C SAE J1128 TENSILITY

Mechanical Tests

After aging at 155±3°C for 7 days
 Minimum tensile strength 10 MPa
 Minimum elongation 150% original
 Dielectric test: 1000 Vrms for 1 minute without breakdown
 Flammability: SAE J1128 Resistance to Flame Propagation
 Ozone resistance: 192 hrs @ 65°C, 100 pphm, no cracks or splits

Fluid Compatibility Tests (Name: fluid, test temp (°C))

Engine oil: ASTM D471 IRM-902, 50±3
 Gasoline: ASTM D471 Ref Fuel C, 23±5
 Ethanol: 85% ethanol + 15% ASTM D471, Ref Fuel C, 23±5
 Diesel fuel: 90% ASTM D471 IRM 903 +10% p-xylene, 23±5
 Power steering: ASTM D471 IRM 903, 50±3
 Auto trans: Dexron VI SAE J311, 50±3
 Engine coolant: 50% dist. water + 50% ethylene glycol, 50±3
 Battery acid: H2SO4 spec. gravity = 1.26±0.005, 23±5



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	12/10/2021	Initial release	Verified:	RoHS compliant Halogen free	
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	Size: Part number:
				Wire, hook-up, TS, 20 AWG, TXL automotive SAE J1128, 60V, 125C, 1.8 mm, XLPE, white	A 30-02204
				Scale: 20:1	Sheet 1 of 1

5

4

3

2

1