

Ratings

Voltage: 300 V
Temperature: -25 ~ 80 °C
Flammability: VW-1

Conductor

Conductor count: 2
Gauge: 14 AWG 2.08 mm²
Material: tinned copper strands
Strand size: Ø 0.254 mm x 41
Resistance at 20 °C: 8.96 Ω /km max

Insulator

Material: PVC
Color: black, red
Diameter: Ø 2.8 ±0.10 mm
Nominal thickness: 0.43 mm
Resistance at 20 °C: 10 MΩ /km min

Filler

Material: cotton rope

Wrap

Material: cotton paper



Outer jacket

Material: PVC
Color: black
Diameter: Ø 7.5 ±0.30 mm
Nominal thickness: 0.76 mm

Wire marking: E339579 UL AWM STYLE 2464 14 AWG 80°C
300V VW-1 --- cUL AWM I/II A 80°C 300V FT1 TENSILITY

Tests

Insulation tensile strength: 2.11 kgf/mm²
Jacket tensile strength: 1.05 kgf/mm²
After aging at 113 ±2 °C for 7 days:
Minimum tensile strength 70 % original
Minimum elongation 65 % original
Heat shock: 121 ±1 °C /1 hour, no observed degradation
Deformation: 121 ±1 °C /1 hour, ≤ 50 %
Cold bend: -10 ±2 °C /1 hour, no observed cracking



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	04/01/2025	Initial release	Verified:	RoHS compliant Function test: no open, no short circuit, no intermittent			
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Wire, 2C TS, 14 AWG, UL2464, 300V, 80C, 7.5 mm, VW-1, PVC	Size: A	Part number: 30-03588	
					Scale: 8:1		Sheet 1 of 1

5

4

3

2

1