Style
M5 socket, flush panel mount
3 pin, A-coding

Ratings
Voltage: 60 V
Current: 1 A
Ingress protection: IP67

Operating Temperature Range
-40 - 105 C°, relative humidity of 85% or less

Materials
1. Insulator: Nylon, PA66 + 33% GF, black
2. Shell: C3771 brass, nickel plated
3. Pin: C3771 brass, gold plated
4. Nut: C3771 brass, nickel plated
5. O-ring: Silicone rubber
6. Epoxy: Epoxy resin

Electrical Requirements
Dielectric strength: 1 min @ 500 Vac
Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 10 mΩ or less

Mechanical Requirements
Life cycle: 500 mating cycles

Environmental Requirements
Salt spray test: 35 °C, relative humidity 90-95%, 5% NaCl mist for 48 hours

Compatibility
Maximum wire gauge: 26 AWG





Front view
Not to scale





Panel Cut-out (M7)
Panel thickness 3 mm
Torque: 0.03 Nm







Back of Connector

Revision:	Date:	Description:
A	03/27/2026	Initial release

Prepared: CR
Digitally signed by CR
Date: 2026.04.08 11:53:28 -07'00'

Verified: KW
Digitally signed by KW
Date: 2026.04.09 09:23:33 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.3 mm
X.X: ± 0.1 mm
X.XX: ± 0.05 mm

Notes:
RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:
Connector, M5 A-code socket, 3 pin, 5xL14.3 mm, panel mount, solder cup, gold plated, IP67

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 54-00543
Scale: 4:1
Sheet 1 of 1

5 4 3 2 1