Style
M8 socket, flush panel mount
5 pin, B-coding

Ratings
Voltage: 30 V
Current: 3 A
Ingress protection: IP67

Operating Temperature Range
-40 - 105 C°, relative humidity of 85% or less

Materials
1. Insulator: Nylon, PA66 + 33% GF, black
2. Shell: C3771 brass, nickel plated
3. Pin: C3771 brass, gold plated
4. Nut: C3771 brass, nickel plated
5. O-ring: Silicone rubber
6. Epoxy: Epoxy resin

Electrical Requirements
Dielectric strength: 1 min @ 500 Vac
Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 10 mΩ or less

Mechanical Requirements
Life cycle: 500 mating cycles

Environmental Requirements
Salt spray test: 35 °C, relative humidity 90-95%, 5% NaCl mist for 48 hours

Compatibility
Maximum wire gauge: 24 AWG



Front View
Not to Scale





Panel cutout (M11)
Panel thickness (5mm max.)
Torque: 0.09 Nm





Back of Connector

Revision:	Date:	Description:
A	03/27/2026	Initial release

Prepared: CR
Digitally signed by CR
Date: 2026.04.08 11:23:50 -07'00'

Verified: KW
Digitally signed by KW
Date: 2026.04.09 10:37:54 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.3 mm
X.X: ± 0.1 mm
X.XX: ± 0.05 mm

Notes:
RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:
Connector, M8 B-code socket, 5 pin, 8xL18.7 mm, panel mount, solder cup, gold plated, IP67

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 54-00554
Scale: 3:1
Sheet 1 of 1

5 4 3 2 1