

Style

Power DIN, plug
4 pin
Auto latch push-pull locking system

Ratings

Voltage: 48 V
Current: 8 A
Flammability: UL94 V-0

Operating Temperature Range

-20~80°C

Materials


- ① Insulator: PBT+25% glass fiber black (UL94 V-0)
- ② Pin: C3604 Brass, nickel plated
- ③ Shell: C3604 Brass, nickel plated
- ④ Housing: ABS, black
- ⑤ Ring: POM
- ⑥ Spring: carbon steel, nickel plated
- ⑦ Strain relief: PVC, black

Electrical Requirements

Dielectric strength: 1 min @ 500 Vac
Insulation resistance: 100 MΩ @ 250 Vdc
Contact resistance: 30 mΩ or less

Mechanical Requirements

Life cycle: 500 mating cycles minimum
Max gauge size: 17 AWG
Max outer jacket diameter: $\varnothing 4$ mm



Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	10/14/2024	Initial release	Verified:				
			Dimensions are in millimeters. Tolerances: X: ± 0.3 mm X.X: ± 0.1 mm X.XX: ± 0.05 mm	Description:	Size:	Part number:	
				Connector, power DIN plug, 4 pin, 4.0 mm SR, nickel plated, assembly type	A	55-00421	
					Scale: 1.5:1		Sheet 1 of 1

5

↑

4

3

2

1