


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00981	Connector, M12 A-code socket, 5 pin, 12xL22 mm, molding style, solder cup, gold plated, IP67, shielded	1	
2	50-00988	Connector, M12 A-code plug, 5 pin, 12xL22 mm, molding style, solder cup, gold plated, IP67, shielded	1	
3	30-03014	Wire, 5C TS, 22 AWG, UL21765, 300V, 105C, 60C oil, UV, 6.7 mm, shielded, VW-1, TPU	1	
4	24-00349	Overmold, M12 plug and jack, 180°	2	TPU, black





Notes:

Cable rated for 60 V, 4 A
Temperature: -40 ~ 105 °C
Oil resistant up to 60 °C
Water resistant up to 75 °C
UV resistant

IP67 waterproof rating when mated with corresponding
(IP67) connector

Functionally equivalent components may be substituted

Wiring Diagram		
50-00981	wire color	50-00988
1	red	1
2	yellow	2
3	black	3
4	white	4
5	blue	5
Shell	shield/drain	Shell

Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	<div>TENSILITY</div> <div>tel 1.541.323.3228800 877.670.7118</div> <div>fax 1.541.323.4202web tensility.com</div>			
A	01/07/2025	Initial release	Verified:					
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 10000 mm, 1.0 mm 5C 50-00981 M12 socket to 1.0 mm 50-00988 M12 plug, 22 AWG, 30-03014 wire	Size:	Part number:		
					A	10-06206		
					Scale: 1:1			Sheet 1 of 1