

Ratings

Voltage: 300 V

Temperature

Static: -40 to 105 °C

Dynamic: -20 to 105 °C

Flammability: VW-1

Water resistant: 75 °C

Oil resistant: 60 °C (jacket)

≥50% elongation and tensile strength after aging

UV resistance: jacket, 720 hours xenon or carbon arc exposure

≥80% tensile strength and elongation after aging

Conductor

Conductor count: 4

Gauge: 26 AWG 0.13 mm²

Material: tinned copper strands

Strand size: Ø 0.08 mm x 26

Resistance at 20 °C: 150 Ω /km Max

Insulator

Material: PVC

Color: red, black, white, yellow

Diameter: Ø 1.3 ±0.10 mm

Nominal thickness: 0.38 mm

Resistance at 20 °C: 10 MΩ /km Min

Wrap

Material: Cotton paper

Outer jacket

Material: PVC, 80A



Color: Black

Diameter: Ø 4.9 ±0.20 mm

Nominal thickness: 0.80 mm

Wire marking: E339579 UL AWM STYLE 20387 26 AWG 105°C
300V VW-1 60°C OIL RESISTANT UV RESISTANT TENSILITY

Use: External wiring



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	10/01/2021	Initial release	Verified:	RoHS compliant Function test: no open, no short circuit, no intermittent			
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description:	Size:	Part number:	
				Wire, 4C TS, 26 AWG, UL20387, 300V, 105C, 60C oil, UV, 4.9 mm, VW-1, PVC, 80A, black	A	30-01660	
					Scale: 10:1		Sheet 1 of 1

5

4

3

2

1