

Ratings

Voltage: 600 V
Temperature: -60 ~ 200 °C
Flammability: FT2

Conductor

Conductor count: 1
Gauge: 20 AWG, 0.52 mm²
Material: tinned copper strands
Strand size: Ø0.178 mm x 21
Resistance at 20 °C: 36.7 Ω /km max



Insulator

Material: Silicone rubber
Color: green
Diameter: 2.48 ±0.1 mm
Nominal thickness: 0.76 mm
Resistance at 20 °C: 10 MΩ /km min

Wire marking: E339579 UL AWM STYLE 3530 20AWG 200°C 600V
SILICONE RUBBER --- cUL AWM I A 200°C 600V FT2 TENSILITY

Bend radius

Static: 12 times diameter (29.76 mm)
Dynamic: 15 times diameter (37.2 mm)



Revision:	Date:	Description:	Prepared:	Notes: RoHS compliant	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	05/22/2024	Initial release	Verified:				
			Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	Size: Part number: A 30-03467		
				Description: Wire, hook-up TS, 20 AWG, UL3530, 600V, 200C, 2.48 mm, FT2, Silicone, green			
					Scale: 15:1		Sheet 1 of 1

5

4

3

2

1