

M12 Plug
4 pin
S-coding

Voltage: 630 Vac
Current: 12 A

-40 ~ 105 °C



- ① Insulator: Polyamide 66 (PA66), UL94 HB, black
- ② Pin: C3604 brass, gold plated
- ③ Shell: C3604 brass, nickel plated
- ④ Hex nut: C3604 brass, nickel plated
- ⑤ O-ring: Silicone rubber
- ⑥ Epoxy: Epoxy resin

Insulation resistance: 100 MΩ @ 500 Vdc
Contact resistance: 10 mΩ or less



Life cycle: 500 mating cycles minimum

Salt spray test: 35 °C, relative humidity 90-95% NaCl mist for 48 hrs. Wash parts after test. Maintain mechanical requirements and a contact of less than 10mΩ
Waterproof: IP67




Wire gauge: 18 AWG max



Panel cutout (PG9)
Panel thickness (4.5mm max.)



SECTION A-A



Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A	03/12/2025	Initial release	Verified:	RoHS compliant			
			Dimensions are in millimeters. Tolerances: X: ± 0.3 mm X.X: ± 0.1 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent			
				Description: Connector, M12 S-code plug, 4 pin, 12xL25.8 mm, panel mount, solder cup, gold plated, IP67	Size:	Part number:	
					A	54-00435	
					Scale: 2:1		